

# Technical Data Sheet

## Enviro-Clean MM

Enviro-Clean MM is a high performance aqueous cleaner specially formulated for the spray cleaning of cast iron, steels, stainless steels, tinplate, copper and its alloys. Enviro-Clean MM removes a wide range of soils, hydrocarbons, oils greases and particulates at low temperatures. The product has low foaming characteristics and includes NT's advance corrosion inhibition system to give excellent residual corrosion protection to parts that have been cleaned with the product. Enviro-Clean MM is free of caustic chemicals, silicates and aggressive biocides and is therefore safe for the user and the environment.

### TYPICAL PROPERTIES

|                   |  |
|-------------------|--|
| <b>Type</b>       | Liquid Cleaner for the spray cleaning of a wide variety of materials including cast iron, steel, stainless steel, tinplate, copper and its alloys. |
| <b>Appearance</b> | Clear light brown liquid   |
| <b>pH</b>         | Concentrate is typically pH 11 to 12.2   |
| <b>SG</b>         | Typically 1.085 to 1.15  |
| <b>Solubility</b> | 100% miscible in water   |

### RECOMMENDATIONS FOR USE

|                    |   |
|--------------------|---|
| <b>Dilution</b>    | Enviro-Clean MM should be used at concentrations of 3% to 5% volume for volume in water. As the product is sequestered, the use of town mains water as a diluent will not cause any problems.                     |
| <b>Temperature</b> | Temperature between 40C and 70C are recommended   |
| <b>Time</b>        | Enviro-Clean MM removes a wide range of soils within the time range 30 to 120 seconds. In general the higher the cleaning temperature and the greater the spray pressure and flow, the shorter the cleaning time. |
| <b>Application</b> | Enviro-Clean MM is designed for spray or flood cleaning   |

HEALTH AND SAFETY: - Oil contaminated rinse water should be collected and disposed of in accordance with Local Authority Regulations. Enviro-Clean MM will generally not cause any Health and Safety issues, when used in accordance with the recommended instructions. More detailed information can be obtained from the appropriate Material Safety Data Sheet.

John Neale Ltd, Halesowen, West Midlands  
Phone / Fax: 0121 585 8793, Mobile: 07941774592  
E-Mail: [info@johnnealeltd.co.uk](mailto:info@johnnealeltd.co.uk) Web:- [www.johnnealeltd.co.uk](http://www.johnnealeltd.co.uk)

Company No: 4476463

**Enviro-Clean MM**