

Envirocut ML30

TECHNICAL DATA SHEET

Envirocut ML30

Description

A non-HAP, non-VOC, biodegradable, renewable, fully synthetic ester based product suitable for high performance grinding and machining. The product gives ultimate surface finish and tool-life. It is based on fully saturated esters and offers significant benefits over other environmentally acceptable lubricants in terms of oxidative stability and odour.

Envirocut ML30 has no air mist hazard.

Envirocut ML30 has a very high flashpoint and auto-ignition temperature, compared to similar viscosity mineral oil based products, which makes it safer in use.

Benefits

- Proven safety for environmental and operator concerns.
- Bio-degradable lubricant
- No air-mist hazard
- Low fuming
- Very high flash point and auto-ignition temperature.
- Safer operation.
- No hazard labelling required
- Operators with sensitive skin appreciate the non-hydrocarbon emollient basis of the fluid.
- Pure chemical so very tight boiling range, no viscosity or performance drift
- Low viscosity ensures maximum flushing
- No artificial dyes to restrict work-piece viewing
- Very low odour
- Longer fluid life

Typical Physical Properties

Appearance	Almost water white
Specific Gravity	~0.87 @ 20°C
Foaming Tendency	Low
Viscosity at 40°C	30 cSt
Lubricity	Very High
Usage Concentration	As supplied

Application Method

Envirocut ML30 is suitable for machining of all metals.

Envirocut ML30 can be applied in mist and flood applications.

John Neale Ltd, 25 Fairfield Road, Halesowen, West Midlands, B63 4PT
info@johnnealetd.co.uk www.johnnealetd.co.uk