

Solvent 702

A non-VOC, non Hazard labeled, solvent.

Solvent 702 is a high performing non-VOC solvent for the removal of the most difficult soils from metals. Designed specifically to replace trichloroethylene at a stainless steel tube mill in the UK it had to be able to a range of heavy duty chlorinated drawing lubricants. It is therefore an ideal choice when removing heavy drawing oils and coolants from metal components. Its high boiling and flash points make it an excellent choice for use at the temperatures at which optimum degreasing performance and drying can be obtained.

Solvent 702 can be used in existing trichloroethylene and other chlorinated solvent degrease equipment, however it is not a vapour phase degreaser, and it operates as a liquid phase solvent.

Solvent 702 is effective in removing the following types of products, this list is not exhaustive.

Gear Oils – mineral oil based	Gear Oils – Synthetic all types
Hydraulic Oils	Machine oils
Metal working coolants	Drawing oils (except copper tube lubricants)
Chlorinated lubricants	Sulphurised lubricants
Forming oils	Tube bending lubricants
Fine blanking oils	Honing fluids

Solvent 702 has optimum degreasing performance at 60-80°C. At this temperature the time required for degreasing is the same as for trichloroethylene and for oil and resin based products the solvency is much the same.

Solvent 702 can replace the following solvent based cleaners.

Trichloroethylene
Perchloroethylene
Methylene chloride

Solvent 702 – Typical Data

Boiling point @ 760 mmHg, 1.01 bar	>220°C
Flash point (Closed Cup)	>100°C
Freezing point	<-10°C
Vapor pressure@ 20°C	extrapolated 0.01 mmHg
Specific gravity (25/25°C)	0.985
Viscosity (cP or mPa.s @ 25°C)	<10
Autoignition temperature	>250°C

John Neale Ltd
25 Fairfield Road, Halesowen, West Midlands, B63 4PT
Tel:- +44 (0) 121 585 8793
Email:- info@johnnealeltd.co.uk
Web:- www.johnnealeltd.co.uk