

Superdraw FS

Superdraw FS

DESCRIPTION

Superdraw FS is a high performance water soluble pressing and drawing lubricant, utilising novel lubricity enhancers to provide excellent performance without chlorine. It has been specifically for punching, nibbling and shearing operations. It also helps in forming operations, as a lubricated sheet marks much less than a non-lubricated sheet.

TYPICAL DATA

<u>Concentrate</u>	
Appearance	Amber fluid
Specific Gravity	1.050
Mineral Oil Content %	Nil
<u>Emulsion</u>	
Appearance	Translucent
pH at 10%	8.8
Reichert Wear Test @ 10%	
Wear ratio, %	15
Noise reduction, m	9

Advantages

- Easy stripping
- Longer tool life
- High film strength for metal forming
- Easier degreasing prior to painting
- Can be used on carbon, steel, copper, brass and aluminum
- No stickiness due to tacky oils

Fire Risks and Hazards

- Use of highly inflammable and hazardous solvents is not required
- No irritating smoke during subsequent operations
- No oil mist

John Neale Ltd, 25 Fairfield Road, Halesowen, West Midlands, B63 4PT.

TDS rev1 – 14-2-05

Tel +44 (0) 121 585 8793

Info@johnnealeltd.co.uk www.johnnealeltd.co.uk