

TECHNICAL DATA SHEET

Vanishing Oil CN-60

Description

A modern high quality, high performance vanishing oil to give significant enhancements in tool-life, operator comfort, and surface finish. It has been designed to give a trace residue on evaporation.

Vanishing Oil CN-60 is a special product which is more rapidly evaporating product compared to CN-80. It is a low-odour, high performance product where good tool-life, and surface finish are preferred.

Our Vanishing Oils are suitable for blanking, forming, punching, and pressing of ferrous and non-ferrous metals, giving superior surface finish and tool-life. The specific grade required should be selected according to the application.

Benefits

Vanishing Oil CN-60
➤ Low Odour
➤ Faster Drying
➤ Multi-metal
➤ Non Staining
➤ Very Low residues

Typical Physical Properties

	Vanishing Oil CN-60
Appearance	Pale Liquid
Specific Gravity	~0.83 @ 20°C
EP Performance	Moderate
Viscosity at 40°C	2cSt
Lubricity	Good
Sulphur (active)	Nil
Usage Concentration	As supplied

Application Method

Our Vanishing Oils can top-up all common vanishing without adverse effect, although the benefits of using a John Neale Ltd product will not then be fully appreciated.

The oil can be applied by brush, swab, roller, or automatic applicator.

John Neale Ltd, 25 Fairfield Road, Halesowen, West Midlands, B63 4PT, UK.
Telephone +44 (0) 121 585 8793
Email:- technical@johnnealeltd.co.uk
Website:- www.johnnealeltd.co.uk

Vanishing Oil CN-60