

TECHNICAL DATA SHEET

Vanishing Oil UXT

Description

A modern high quality, ultra high performance vanishing oil which gives significant enhancements in tool-life, operator comfort, and surface finish due to a special combination of chlorine-free additives. Vanishing Oil UXT gives truly excellent performance.

Vanishing Oil UXT is a special product which is rapidly evaporating and very low-odour. It is a very high performance product yielding very good tool-life and excellent surface finish.

Our Vanishing Oils are suitable for blanking, forming, punching, and pressing of ferrous and non-ferrous metals, giving superior surface finish and tool-life. The specific grade required should be selected according to the application; please contact John Neale Ltd to discuss your specifics to ensure best product selection.

Benefits

Vanishing Oil UXT
➤ Low Odour
➤ Faster Drying
➤ Multi-metal
➤ Non Staining
➤ Zero residues

Typical Physical Properties

	Vanishing Oil UXT
Appearance	Pale Liquid
Specific Gravity	~0.83 @ 20°C
EP Performance	Moderate
Viscosity at 40°C	2cSt
Lubricity	Moderate
Sulphur (active)	Nil
Usage Concentration	As supplied

Application Method

Our Vanishing Oils can top-up all common vanishing without adverse effect, although the benefits of using a John Neale Ltd product will not then be fully appreciated.

The oil can be applied by brush, swab, roller, or automatic applicator.

Vanishing Oil UXT